

C.1 Thermostatic shower mixer for concealed installation # C142000150.. / C142000150..

|< 150 mm >|



| Thermostatic shower mixer for concealed installation | Dimension | Weight | Order number |
|--|--------------|----------|--------------|
| Number of outlets: 1, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts | | | |
| Colors | | | |
| 10 Chrome 46 Black Matt | | | |
| Variant | | | |
| Chrome, Flow rate (3 bar): 20,5 l/min, 150x150 mm | | 1.800 kg | C142000150.. |
| Black Matt, Flow rate (3 bar): 20,5 l/min, 150x150 mm | | 1.800 kg | C142000150.. |
| Necessary accessory for Chrome, Flow rate (3 bar): 20,5 l/min, 150x150 mm | | | |
| Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No | 164 x 105 mm | 1.24 kg | GK0900000 |
| Basic Set Shut-off valve: Yes | 164 x 105 mm | 1.4 kg | GK0900001 |
| Suitable accessories | | | |
| Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs | 245 x 110 mm | 0.16 kg | UV0650013 |
| Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs | 245 x 110 mm | 0.2 kg | UV0650015 |
| Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs | 245 x 110 mm | 0.2 kg | UV0652015 |

C.1 Thermostatic shower mixer for concealed installation # C142000150.. / C142000150..

| < 150 mm > |

| | | | |
|--|--------------|---------|-----------|
| Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs | 240 x 120 mm | 0.24 kg | UV0650017 |
| Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs | 240 x 120 mm | 0.24 kg | UV0652017 |
| Shower rail Hand shower holder: height adjustable | 700 x 70 mm | 0.32 kg | UV0600003 |
| Shower rail 100 mm, Hand shower holder: height adjustable | 100 x 70 mm | 0.36 kg | UV0600004 |
| wall outlet Round, Non-return valve: Individually, in the hose connection, Escutcheon shape: Round, Dimensions of water supply connection: DN 15 | 55 x 80 mm | 0.27 kg | UV0630008 |
| wall outlet Square, Non-return valve: Individually, in the hose connection, Escutcheon shape: Square, Dimensions of water supply connection: DN 15 | 55 x 80 mm | 0.27 kg | UV0630011 |
| Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical | 1250 x 23 mm | 0.28 kg | UV0610006 |
| Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical | 1600 x 23 mm | 0.34 kg | UV0610007 |
| Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical | 1800 x 23 mm | 0.37 kg | UV0610008 |
| Shower rail Hand shower holder: height adjustable | 810 x 60 mm | 1.1 kg | UV0600005 |
| Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs | 245 x 110 mm | 0.16 kg | UV0652013 |
| Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs | 245 x 110 mm | 0.16 kg | UV0650014 |
| Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs | 245 x 110 mm | 0.16 kg | UV0652014 |
| Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs | 245 x 110 mm | 0.2 kg | UV0650016 |
| Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs | 245 x 110 mm | 0.2 kg | UV0652016 |

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

C.1 Thermostatic shower mixer for concealed installation #
C142000150.. / C142000150..

|< 150 mm >|

