

## C.1 Thermostatic shower mixer for concealed installation # C142000160.. / C142000160..

|< 170 mm >|



Thermostatic shower mixer for concealed installation	Dimension	Weight	Order number
Number of outlets: 1, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off valve, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts			
<b>Colors</b>			
10 Chrome 46 Black Matt			
<b>Variant</b>			
Chrome, Flow rate (3 bar): 20,5 l/min		1.800 kg	C142000160..
Black Matt, Flow rate (3 bar): 20,5 l/min		1.800 kg	C142000160..
<b>Necessary accessory for Chrome, Flow rate (3 bar): 20,5 l/min</b>			
Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000
Basic Set Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001
<b>Suitable accessories</b>			
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015

## C.1 Thermostatic shower mixer for concealed installation # C142000160.. / C142000160..

|< 170 mm >|

Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Shower rail Hand shower holder: height adjustable	700 x 70 mm	0.32 kg	UV0600003
Shower rail 100 mm, Hand shower holder: height adjustable	100 x 70 mm	0.36 kg	UV0600004
wall outlet Round, Non-return valve: Individually, in the hose connection, Escutcheon shape: Round, Dimensions of water supply connection: DN 15	55 x 80 mm	0.27 kg	UV0630008
wall outlet Square, Non-return valve: Individually, in the hose connection, Escutcheon shape: Square, Dimensions of water supply connection: DN 15	55 x 80 mm	0.27 kg	UV0630011
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1600 x 23 mm	0.34 kg	UV0610007
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1800 x 23 mm	0.37 kg	UV0610008
Shower rail Hand shower holder: height adjustable	810 x 60 mm	1.1 kg	UV0600005
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

**C.1 Thermostatic shower mixer for concealed installation #**  
**C142000160.. / C142000160..**

| < 170 mm > |

