

**SensoWash® Classic Shower toilet seat** # 613000012000300 /  
613000012000304 / 613000012004300

|< 365 mm >|



Shower toilet seat	Dimension	Weight	Order number
Suitable for series ME by Starck, Starck 2, Starck 3, Darling New, Bento Starck Box, Automatic close, Adjustable shower jet position level: 5 Steps, Controllable spray jet intensity steps: 3 Steps, Controllable spray jet temperature steps: 4 Steps, Adjustable shower jet position level: 5 Steps, Rearwash, Ladywash, Pulsing shower spray: Oscillating, Number of programmable user profiles: 4, Self-cleaning shower nozzle/shower head, Decalcification function, Energy saving mode: Adjustable, Night light			
<b>Colors</b>			
01 White			
<b>Variant</b>			
White, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Warm air dryer, Seat heater, Remote control, App, Odour extraction, Holiday mode, Protection type: IPX4		5.000 kg	613000012000300
White, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Warm air dryer, Seat heater, Remote control, App, Odour extraction, Holiday mode, Protection type: IPX4		0.999 kg	613000012000304
White, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Warm air dryer, Seat heater, Remote control, App, Odour extraction, Holiday mode, Protection type: IPX4		5.000 kg	613000012004300
<b>Installation accessories</b>			
Pre-installation set	135 x 105 mm	0.43 kg	005072
Vario Connector Set	260 x 220 mm	0.385 kg	100730
Vario Connector Set	220 x 260 mm	0.7 kg	100691
<b>Suitable products</b>			
Toilet wall-mounted for shower toilet seat Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Outlet drain horizontal, Incl. invisible fixation, Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1, 365 x 620 mm	365 x 620 mm		254459
Toilet wall-mounted for shower toilet seat Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Flush principle: washdown model, Outlet drain horizontal, Incl. invisible fixation, Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1, 365 x 620 mm	365 x 620 mm		222659

## SensoWash® Classic Shower toilet seat # 613000012000300 / 613000012000304 / 613000012004300

| < 365 mm > |

<p>Toilet wall-mounted for shower toilet seat Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Flush principle: washdown model, Outlet drain horizontal, Incl. invisible fixation, 375 x 620 mm Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1, 375 x 620 mm</p>	253359
<p>One piece toilet for shower toilet seat SensoWash Toilet, 705 mm, Elongated, Single Flush, Flush water quantity: 4,8 l, extractor/siphon jet, Flushing rim: Closed, Outlet drain: vertical, 395 x 705 mm Flush operation position: LeftRight, Distance of rear panel/outlet: 305 mm, 395 x 705 mm</p>	212051
<p>Toilet wall-mounted for shower toilet seat Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Flush principle: washdown model, Outlet drain horizontal, Incl. invisible fixation, 373 x 570 mm Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1, 373 x 570 mm</p>	252859
<p>Toilet wall-mounted for shower toilet seat Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Rimless, Incl. invisible fixation, Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1,</p>	252959
<p>Toilet floorstanding for shower toilet seat Back to wall version, Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Outlet drain: horizontal, Position outlet: Back, Flush principle: washdown model, Incl. mounting material, Unified Water Label (UWL) Class: 1, 370 x 600 mm</p>	216959
<p>Two piece toilet for shower toilet seat SensoWash Toilet, 710 mm, Elongated, Flush water quantity: 4,8/4,8 l, extractor/siphon jet, Flushing rim: Closed, Outlet drain vertical, 373 x 710 mm</p>	217151
<p>One piece toilet for shower toilet seat SensoWash Toilet, 730 mm, Elongated, Flush water quantity: extractor/siphon jet, Flushing rim: Rimless, Outlet drain: vertical, Distance of rear panel/outlet: 305 mm, 390 x 730 mm</p>	217351
<p>Toilet wall-mounted for shower toilet seat HygieneFlush Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Rimless, Flush principle: washdown model, Incl. invisible fixation, Incl. connecting set for SensoWash, Unified Water Label (UWL) Class: 1, 370 x 570 mm</p>	257959
<p>Toilet floorstanding for shower toilet seat White High Gloss, Back to wall version, Flush water quantity: 4,5/3 l, Washdown model, Flushing rim: Closed, Outlet drain: horizontal, Position outlet: Back, Flush principle: washdown model, For bowl mounted cistern, Incl. mounting material, Unified Water Label (UWL) Class: 1, 370 x 600 mm</p>	201459

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.