


## Faucet Accessories Showerhead # UV0660021010 / UV0660021C10

| < 45 mm > |



Showerhead	Dimension	Weight	Order number
Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain			
<b>Colors</b>			
10 Chrome			
<b>Variant</b>			
Type of mounting: Wall installation, Ceiling mount, Round, Diameter of showerhead: 400 mm, Chrome High Gloss		2.050 kg	UV0660021010
Type of mounting: Wall installation, Ceiling mount, Round, Diameter of showerhead: 400 mm, Chrome High Gloss		2.050 kg	UV0660021C10
<b>Suitable accessories</b>			
Shower arms Escutcheon shape: Round	65 x 200 mm	0.18 kg	UV0670025
Shower arms Escutcheon shape: Round	65 x 300 mm	0.154 kg	UV0670026
Shower arms Escutcheon shape: Round	65 x 210 mm	0.15 kg	UV0670027
Shower arms Escutcheon shape: Round	65 x 410 mm	0.23 kg	UV0670028
<b>Suitable accessories for Type of mounting: Wall installation, Ceiling mount, Round, Diameter of showerhead: 400 mm, Chrome High Gloss</b>			
Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 94 mm	1.8 kg	C14200013
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	B14210012

## Faucet Accessories Showerhead # UV0660021010 / UV0660021C10

|< 45 mm >|

Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 87 mm	2.15 kg	B24210012
Thermostatic shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Flow rate (3 bar): 20,6 l/min, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 94 mm	1.8 kg	C14200014
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 77 mm	1.88 kg	C14210011
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 77 mm	1.9 kg	C14210012
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 80 mm	2.1 kg	DE4210012
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 97 mm	2.2 kg	WT4210012
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 86 mm	2.2 kg	TU4210012
Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Tub filler, Hand shower, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 73 mm	1.58 kg	CE4210008

## Faucet Accessories Showerhead # UV0660021010 / UV0660021C10

|< 45 mm >|

Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	125 x 89 mm	1.63 kg	WA4210008
Single lever mixer concealed set Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Outlet/Diverter: Diverter automatically reverts from hand shower to bath spout when turned off, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, 125x171 mm, Including functional unit, Including trim parts	125 x 76 mm	1.61 kg	MH4210008
Single lever shower mixer for concealed installation Number of outlets: 2, Chrome, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts	170 x 86 mm	1.75 kg	N14210012
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round	170 x 82 mm	1.9 kg	CE4210012
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Hand shower, Showerhead, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts	150 x 82 mm	2.15 kg	MH4210012
Single lever shower mixer for concealed installation Number of outlets: 2, Connection type for water supply connection: Basic Set, Ceramic cartridge, Consumer selection: Showerhead, Hand shower, Outlet/Diverter: Diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Including functional unit, Including trim parts	170 x 92 mm	2.2 kg	WA4210012
Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	300 x 300 mm	1.5 kg	UV0660031
Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	200 x 200 mm	0.85 kg	UV0660030
Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	400 x 400 mm	2.05 kg	UV0660021
Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	300 x 300 mm	1.3 kg	UV0660020
Showerhead Stainless steel, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	200 x 200 mm	0.75 kg	UV0660019

## Faucet Accessories Showerhead # UV0660021010 / UV0660021C10

| < 45 mm > |

Showerhead Plastic, Showerhead angle adjustable, MinusFlow, Type of mounting: Ceiling mount, Wall installation, Spray mode: Rain	250 x 250 mm	0.65 kg	UV0662018
Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	250 x 250 mm	0.65 kg	UV0660018
Showerhead Plastic, Showerhead angle adjustable, MinusFlow, Type of mounting: Ceiling mount, Wall installation, Spray mode: Rain	230 x 230 mm	0.56 kg	UV0662017
Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	230 x 230 mm	0.56 kg	UV0660017
Showerhead Plastic, Showerhead angle adjustable, Type of mounting: Ceiling mount, Wall installation, Dimensions of water supply connection: 1/2", Spray mode: Rain	100 x 100 mm	0.15 kg	UV0660022

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

