

Faucet Accessories Hand shower holder # UV06200010.. / UV06200010.. / UV0620001C.. / UV0620001C..

|< 38 mm >|



Hand shower holder	Dimension	Weight	Order number
Plastic, Hand shower holder: Fixed, Mounting bracket shape: Conical			
Colors			
10 Chrome 46 Black Matt			
Variant			
Chrome		0.040 kg	UV06200010..
Black Matt		0.040 kg	UV06200010..
Chrome		0.040 kg	UV0620001C..
Black Matt		0.040 kg	UV0620001C..
Suitable accessories			
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Stick hand shower Dimensions of water supply connection: 1/2", Silicone nubs	187 x 25 mm	0.14 kg	UV0640001
Stick hand shower Dimensions of water supply connection: 1/2", Silicone nubs	212 x 22 mm	0.18 kg	UV0640002
Suitable accessories for Chrome			

Faucet Accessories Hand shower holder # UV06200010.. / UV06200010.. / UV0620001C.. / UV0620001C..

| < 38 mm > |

Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Noise class: II	209 x 171 mm	1.6 kg	B15230000
Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Noise class: II	182 x 170 mm	1.68 kg	B25230000
Single lever bathtub mixer for exposed installation Chrome, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Flow rate (3 bar): 20,9 l/min	208 x 136 mm	1.41 kg	DE5230000
Single lever bathtub mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 10 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Diverter automatically reverts from hand shower to bath spout when turned off	216 x 178 mm	1.3 kg	N15230000
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Single lever bathtub mixer for exposed installation Chrome, Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 20 mm, Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off, Flow rate (3 bar): 15,5 l/min	210 x 166 mm	1.3 kg	A15230001
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve	290 x 201 mm	1.96 kg	CE5230000
Suitable accessories for Chrome, Chrome			
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Suitable accessories for Chrome, Black Matt			

Faucet Accessories Hand shower holder # UV06200010.. / UV06200010.. / UV0620001C.. / UV0620001C..

|< 38 mm >|

Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve, Noise class: II	314 x 190 mm	2.35 kg	C15230000
Bathtub thermostat for exposed installation Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Shut-off and diverter valve, Noise class: II	338 x 190 mm	2.55 kg	C15220000
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter valve	313 x 191 mm	3.9 kg	TU5230000
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	187 x 25 mm	0.14 kg	UV0642001
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	212 x 22 mm	0.18 kg	UV0642002
Bathtub thermostat for exposed installation Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Centre distance: 150 mm ± 15 mm, Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Safety lock at 38 °C, Diverter valve, Non-return valve in the hose connection, Shut-off and diverter valve, Flow rate (3 bar): 18 l/min	303 x 223 mm	2.58 kg	WA5220000
Single lever bathtub mixer for exposed installation Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off	216 x 198 mm	1.76 kg	WA5230000
Single lever bathtub mixer for exposed installation Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve	286 x 213 mm	2.57 kg	MH5230000
Suitable accessories for Chrome, Black Matt			
Hand shower Spray mode: SilkRain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	260 x 130 mm	0.3 kg	UV0650018
Hand shower Silicone nubs		0.29 kg	UV065G018
Hand shower holder Brass, Hand shower holder: Fixed, Escutcheon shape: Square, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620026

Faucet Accessories Hand shower holder # UV06200010.. / UV06200010.. / UV0620001C.. / UV0620001C..

| < 38 mm > |

Hand shower holder Brass, Hand shower holder: Fixed, Escutcheon shape: Round, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620007
Hand shower holder Plastic, Hand shower holder: Fixed, Mounting bracket shape: Conical	38 x 58 mm	0.04 kg	UV0620001
Hand shower holder Plastic, Hand shower holder: Fixed, Mounting bracket shape: Conical	52 x 34 mm	0.027 kg	UV0620000

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

