

Wave Thermostatic shower mixer for exposed installation #  
WA4220000A.. / WA4220000A.. / WA4220000A.. / WA4220000A..  
/ WA4220000A..

|< 65 mm >|



Thermostatic shower mixer for exposed installation	Dimension	Weight	Order number
Water connection: S-connections, 1/2", Centre distance: 150 mm ± 15 mm, Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection			
Colors			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
Variant			
only for Asian markets, Bronze Brushed, Flow rate (3 bar): 6 l/min	303x65 mm	2.200 kg	WA4220000A..
only for Asian markets, Chrome, Flow rate (3 bar): 6 l/min	303x65 mm	2.200 kg	WA4220000A..
only for Asian markets, Gold Polished, Flow rate (3 bar): 6 l/min	303x65 mm	2.200 kg	WA4220000A..
only for Asian markets, Black Matt, Flow rate (3 bar): 6 l/min	303x65 mm	2.200 kg	WA4220000A..
only for Asian markets, Stainless steel Brushed, Flow rate (3 bar): 6 l/min	303x65 mm	2.200 kg	WA4220000A..

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

