

Wave Single lever bathtub mixer for exposed installation #
 WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
 / WA52300000.. / WA52300000C.. / WA52300000C..

|< 113 mm >|



Single lever bathtub mixer for exposed installation	Dimension	Weight	Order number
Connection type for water supply connection: S-connections, Dimension of connection hose: 1/2", Ceramic cartridge, recommended operating pressure: 1 - 5 bar, Spray mode: Normal spray, Diverter valve, Non-return valve in the hose connection, Diverter automatically reverts from hand shower to bath spout when turned off			
Colors			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
Variant			
bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min		1.930 kg	WA52300000..
Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min		1.930 kg	WA52300000..
Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min		1.930 kg	WA52300000..
Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min		1.930 kg	WA52300000..
Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min		1.930 kg	WA52300000..
Chrome, Centre distance: 150 mm ± 15 mm		1.930 kg	WA52300000C..
Black Matt, Centre distance: 150 mm ± 15 mm		1.930 kg	WA52300000C..
Suitable accessories for bronze Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Chrome, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Gold Polished, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Black Matt, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min, Stainless steel Brushed, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 25 l/min			
Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	187 x 25 mm	0.14 kg	UV0642001

Wave Single lever bathtub mixer for exposed installation #
WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
/ WA52300000.. / WA52300000C.. / WA52300000C..

| < 113 mm > |

Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1600 x 23 mm	0.34 kg	UV0610007
Hand shower holder Brass, Hand shower holder: Fixed, Escutcheon shape: Round, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620007
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Stick hand shower Dimensions of water supply connection: 1/2", Silicone nubs	187 x 25 mm	0.14 kg	UV0640001
Stick hand shower Dimensions of water supply connection: 1/2", Silicone nubs	212 x 22 mm	0.18 kg	UV0640002
Stick hand shower MinusFlow, Flow rate (3 bar): 9 l/min, Silicone nubs	212 x 22 mm	0.18 kg	UV0642002
Hand shower holder Plastic, Hand shower holder: Fixed, Mounting bracket shape: Conical	38 x 58 mm	0.04 kg	UV0620001
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1800 x 23 mm	0.37 kg	UV0610008
Hand shower holder Brass, Hand shower holder: Fixed, Escutcheon shape: Square, Mounting bracket shape: Conical	55 x 102 mm	0.3 kg	UV0620026

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Wave Single lever bathtub mixer for exposed installation #
 WA52300000.. / WA52300000.. / WA52300000.. / WA52300000..
 / WA52300000.. / WA52300000C.. / WA52300000C..

| < 113 mm > |

