

**Thermostats Thermostat for concealed installation, 2 outlets #**  
**TH42000140.. / TH42000140.. / TH42000140.. / TH42000140.. /**  
**TH42000140..**

|< 170 mm >|



Thermostat for concealed installation, 2 outlets	Dimension	Weight	Order number
Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Round, Diameter escutcheon: 170 mm, Including functional unit, Including trim parts			
<b>Colors</b>			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
<b>Variant</b>			
bronze Brushed		1.800 kg	TH42000140..
Chrome		1.800 kg	TH42000140..
Gold Polished		1.800 kg	TH42000140..
Black Matt		1.800 kg	TH42000140..
Stainless steel Brushed		1.800 kg	TH42000140..
<b>Necessary accessory for bronze Brushed</b>			
Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000
Basic Set Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*

**Thermostats Thermostat for concealed installation, 2 outlets #**  
 TH42000140.. / TH42000140.. / TH42000140.. / TH42000140.. /  
 TH42000140..

| < 170 mm > |

