

# Thermostats Thermostat for concealed installation, 1 outlet # TH42000150.. / TH42000150..

|< 150 mm >|



Thermostat for concealed installation, 1 outlet	Dimension	Weight	Order number
Number of outlets: 1, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Number of outlets: 1, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts			
<b>Colors</b>			
10 Chrome 46 Black Matt			
<b>Variant</b>			
Chrome, 150x150 mm		1.800 kg	TH42000150..
Black Matt, 150x150 mm		1.800 kg	TH42000150..
<b>Necessary accessory for Chrome, 150x150 mm</b>			
Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000
Basic Set Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

**Thermostats Thermostat for concealed installation, 1 outlet #**  
**TH42000150.. / TH42000150..**

|< 150 mm >|

