

Thermostats Thermostat for concealed installation, 2 outlets # TH42000130.. / TH42000130..

| < 150 mm > |



Thermostat for concealed installation, 2 outlets	Dimension	Weight	Order number
Number of outlets: 2, Connection type for water supply connection: Basic Set, Thermostat cartridge, Safety lock at 38 °C, Outlet/Diverter: Shut-off and diverter valve, Number of outlets: 2, recommended operating pressure: 1 - 5 bar, Escutcheon shape: Square, Including functional unit, Including trim parts			
Colors			
10 Chrome 46 Black Matt			
Variant			
Chrome, 150x150 mm		1.800 kg	TH42000130..
Black Matt, 150x150 mm		1.800 kg	TH42000130..
Necessary accessory for Chrome, 150x150 mm			
Basic Set Dimensions of water supply connection: DN 15, Shut-off valve: No	164 x 105 mm	1.24 kg	GK0900000
Basic Set Shut-off valve: Yes	164 x 105 mm	1.4 kg	GK0900001

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Thermostats Thermostat for concealed installation, 2 outlets #
TH42000130.. / TH42000130..

|< 150 mm >|

