

# SensoWash® Starck f Shower toilet seat Pro # 612002012000370

|< 378 mm >|



Shower toilet seat Pro	Dimension	Weight	Order number
Adjustable blower levels: 2 Steps, Flow rate dryer: 35 m3/h, Controllable warm air dryer steps: 4 Steps, Adjustable shower jet position level: 5 Steps, Controllable spray jet intensity steps: 3 Steps, Controllable spray jet temperature steps: 4 Steps, Adjustable shower jet position level: 5 Steps, Rearwash, Ladywash, Pulsing shower spray: Oscillating, Warm air dryer, Number of programmable user profiles: 2, Self-cleaning shower nozzle/shower head, Decalcification function, Energy saving mode: Adjustable, Holiday mode, Night light			
<b>Colors</b>			
00 White Alpin			
<b>Variant</b>			
Suitable for series ME by Starck, White, Seat material type: Thermoplastic, Lid material type: Thermoplastic, Seat heater, USB remote control, Rated voltage: 220 - 240 V, Frequency: 50 Hz, Protection type: IPX4	378x218 mm	5.600 kg	612002012000370
<b>Installation accessories</b>			
Pre-installation set	105 x 135 mm	0.43 kg	005072
Connector Set Shower toilets	220 x 60 mm	0.28 kg	100731
Interface set	285 x 300 mm	0.35 kg	100729
<b>Suitable products</b>			
Toilet wall-mounted for shower toilet seat HygieneGlaze, Flush water quantity: 4,8/4,8 l, Washdown model, Flushing rim: Rimless, Flush principle: washdown model, Outlet drain horizontal, Incl. invisible fixation, 360 x 575 mm	360 x 575 mm		251009
One piece toilet for shower toilet seat 745 mm, Flush water quantity: 5/3,5 l, extractor/siphon jet, Flushing rim: Rimless, Outlet drain: vertical, Distance of rear panel/outlet: 305 mm, 378 x 745 mm	378 x 745 mm		219001

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.