

Thermostats Thermostatic shower mixer for exposed installation
1000 # TH42200000.. / TH42200000.. / TH42200000.. /
TH42200000.. / TH42200000..

|< 65 mm >|



Thermostatic shower mixer for exposed installation 1000	Dimension	Weight	Order number
Dimension of connection hose: 1/2", Thermostat cartridge, recommended operating pressure: 1 - 5 bar, Safety lock at 38 °C, Non-return valve in the hose connection			
Colors			
04 Brushed Bronze 10 Chrome 34 Polished Gold 46 Black Matt 70 Brushed Stainless Steel			
Variant			
bronze Brushed, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min		2.250 kg	TH42200000..
Chrome, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min		2.250 kg	TH42200000..
Gold Polished, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min		2.250 kg	TH42200000..
Black Matt, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min		2.250 kg	TH42200000..
Stainless steel Brushed, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min		2.250 kg	TH42200000..
Suitable accessories			
Hand shower MinusFlow, Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Flow rate (3 bar): 9 l/min, Silicone nubs	240 x 120 mm	0.24 kg	UV0652017
Shower rail 100 mm, Hand shower holder: height adjustable	100 x 70 mm	0.36 kg	UV0600004
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1600 x 23 mm	0.34 kg	UV0610007
Suitable accessories for Chrome, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min			
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650014

Thermostats Thermostatic shower mixer for exposed installation

1000 # TH42200000.. / TH42200000.. / TH42200000.. / TH42200000.. / TH42200000..

| < 65 mm > |

Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652014
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650016
Suitable accessories for Chrome, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Black Matt, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min			
Hand shower Spray mode: Rain, Dimensions of water supply connection: 1/2", Silicone nubs	245 x 110 mm	0.16 kg	UV0650013
Hand shower MinusFlow, Spray mode: Rain, Dimensions of water supply connection: 1/2", Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.16 kg	UV0652013
Hand shower Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Silicone nubs	245 x 110 mm	0.2 kg	UV0650015
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652015
Hand shower Spray mode: Rain, Pulse, Mono, Dimensions of water supply connection: 1/2", Spray mode selection: Push button, Silicone nubs	240 x 120 mm	0.24 kg	UV0650017
Shower rail Hand shower holder: height adjustable	700 x 70 mm	0.32 kg	UV0600003
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1250 x 23 mm	0.28 kg	UV0610006
Shower hose Rotation lock: Yes, Dimensions of water supply connection: 1/2", Nut shape: Conical	1800 x 23 mm	0.37 kg	UV0610008
Shower rail Hand shower holder: height adjustable	810 x 60 mm	1.1 kg	UV0600005
Suitable accessories for Chrome, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, bronze Brushed, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Gold Polished, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min, Stainless steel Brushed, Connection type for water supply connection: S-connections, Centre distance: 150 mm ± 15 mm, Flow rate (3 bar): 24,5 l/min			
Hand shower MinusFlow, Spray mode: SoftRain, Rain, IntenseRain, Dimensions of water supply connection: 1/2", Spray mode selection: Rotating blasting disc, Flow rate (3 bar): 9 l/min, Silicone nubs	245 x 110 mm	0.2 kg	UV0652016

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.

Thermostats Thermostatic shower mixer for exposed installation
 1000 # TH42200000.. / TH42200000.. / TH42200000.. /
 TH42200000.. / TH42200000..

| < 65 mm > |

