

Balcoon Cistern # 095700..05 / 095700..85 / 095700..05 / 095700..85 / 095700..05 / 095700..85

| < 350 mm > |



Cistern	Dimension	Weight	Order number
DuraShield, Incl. mechanism, Dual Flush, Water connection position: Right, Left 3/8", Flush operation position: Top center, Surface of push button: Chrome			
Colors			
AA White DuraShield (an antibacterial ceramic glaze that provides almost indefinite effectiveness) AC White Satin Matt DuraShield (an antibacterial ceramic glaze that provides almost indefinite effectiveness) AM Clay terra Matt			
Variant			
♣ White, Flush water quantity: 6/3 l, Unified Water Label (UWL) Class: 2	350x360 mm	13.600 kg	095700..05
♣ White, Flush water quantity: 4,5/3 l, Unified Water Label (UWL) Class: 1	350x360 mm	13.600 kg	095700..85
♣ White, Flush water quantity: 6/3 l, Unified Water Label (UWL) Class: 2	350x360 mm	13.600 kg	095700..05
♣ White, Flush water quantity: 4,5/3 l, Unified Water Label (UWL) Class: 1	350x360 mm	13.600 kg	095700..85
♣ Clay terra, Flush water quantity: 6/3 l, Unified Water Label (UWL) Class: 2	350x360 mm	13.600 kg	095700..05
♣ Clay terra, Flush water quantity: 4,5/3 l, Unified Water Label (UWL) Class: 1	350x360 mm	13.600 kg	095700..85
Suitable products			
Toilet close-coupled DuraShield, Flush water quantity: 4,5/3 l, Washdown model, Rimless, Outlet drain: horizontal, Position outlet: Back, Wall, Flush principle: washdown model, For bowl mounted cistern, Outlet dimensions for Vario connecting bend vertical: 160 mm - 230 mm, Outlet dimensions for Vario outlet set vertical/horizontal: 70 mm - 170 mm, Unified Water Label (UWL) Class: 1, 370 x 650 mm	370 x 650 mm		207009

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.